

wondrwall



All-In-One Heat Pump Cylinder



WDR-HT-120-UK
WDR-HT-150-UK

WDR-HT-200-UK
WDR-HT-250-UK

WDR-HT-300-UK

REV 181224

TECHNICAL SPECIFICATION



WDR-HT-120-UK WDR-HT-150-UK WDR-HT-200-UK WDR-HT-250-UK WDR-HT-300-UK

Wondrwall All-In-One Heat Pump Cylinder					
Dimensions mm (W x D x H)	500 x 500 x 1550	500 x 500 x 1670	620 x 620 x 1638	620 x 620 x 1638	620 x 620 x 2038
Net Weight	89kg	92kg	105kg	115kg	130kg
Gross Weight	102kg	107kg	115kg	125kg	140kg
Running Mode	Heating				
Heating Capacity	2.2kW				
Storage Size	120L	150L	200L	250L	300L
COP	4.04kW		4.15kW		
Output Water Temp.	55°C (Max 75°C)				
Power Input	545W		530W		
Max Power Input			3000W		
Rated Current (RLA)	2.6A		2.9A		
Noise Level	48dB(A)				
Refrigerant Type	R290				
Running Ambient Temp.	-7°C -43°C				
Power Supply	220V/50Hz				
Compressor	Rotary (GMCC)			Rotary (Panasonic)	
Packing mm (W x D x H)	560 x 560 x 1740	560 x 560 x 1860	700 x 700 x 1690	700 x 700 x 1920	700 x 700 x 2090
E-heater	2kW				

Notes

1. Test conditions: Outdoor temp. 20/15°C (DB/WB), inlet water temp. 15°C, outlet water temp. 55°C.
2. The specification may be changed for product improvement, please refer to the name plate.